

heat wagon

PORTABLE SPACE VENTED HEATERS

AVAILABLE FOR RENT AT



www.atsequipment.com

1800L

Liquid Propane

SPECIFICATIONS

Input.....	750,000 BTU/Hr
Fuel.....	Liquid Propane
Inlet Pressure.....	Max PS.. Min PSI
Liquid Propane.....	350 lbs.. 5 lbs.
Manifold Pressure.....	Propane 7.0" w.c.
Gas Consumption.....	8.2 GPH
Gas Connection.....	1/4" FNPT
Electrical Requirements.....	120 Volts 20 amp circuit
Fan.....	4200 CFM 1.0 HP 1/2" SP
Thermostat.....	Standard On/Off
Temp Rise.....	385°F
Dimension.....	50"L x 26"W x 30"H
Approximate Weight.....	200 lbs.

heat wagon 



Features

- Air flow switch
- Burner heat shield
- Dual fuel
- Ductable
- Flame safeguard control

- Hi limit switch
- Manifold pressure gauge
- Motor overload - manual reset
- Panel mounted thermostat
- Panel mounted voltage meter
- Weather sealed control box

Benefits

- Safe fuel shutdown if combustion air is interrupted
- Low housing temperature
- Simple lever change from propane to natural gas
- May be ducted up to 50 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Protects heater by shutting down if unit is being overfired
- Helps in diagnosing specific gas flow problems
- Protects heater by shutting down if voltage is too low
- Automatically cycles the heater on/off with a 10 second fan shutdown delay
- Easy monitoring of supply voltage to ensure trouble-free operation
- Indoor/outdoor usage

ATS EQUIPMENT INC. **Construction Equipment & Supplies** **Rentals • Sales • Service**

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

CANDIA, NH
(603) 483-2100