

## P425/HP375WCU TF4 AIR COMPRESSOR





www.atsequipment.com

## EPA COMPLIANT PORTABLE AIR COMPRESSOR

| Model                                | P425/HP375         |                  |
|--------------------------------------|--------------------|------------------|
| COMPRESSOR ROTARY SCREW/SINGLE-STAGE | LOW<br>PRESSURE    | HIGH<br>PRESSURE |
| Free-Air Delivery – cfm              | 425                | 375              |
| Rated Operating Pressure – psig      | 100                | 150              |
| Pressure Range – psig                | 80 - 175           |                  |
| Air Discharge Outlet Size – in       | 1.25               |                  |
| Air Discharge Outlet Quantity        | 1                  |                  |
| Fuel Tank Capacity – gal             | 60                 |                  |
| ENGINE                               |                    |                  |
| Make/Model                           | Cummins/QSB4.5     |                  |
| Emissions Tier Level                 | Tier 4 Final (T4F) |                  |
| Number of Cylinders                  | 4                  |                  |
| Displacement – cu in                 | 2                  | 272              |
| Rated Speed – rpm                    | 2200               | 1950             |
| Idle Speed – rpm                     | 1500               |                  |
| Bhp @ Rated Speed                    | 130                | 138              |
| Electrical - volts                   |                    | 24               |
| Hours of Operation @ Full Load       | 10.9               | 10.6             |
| DIMENSIONS WITH RUNNING GEAR         |                    |                  |
| Length – in                          | 152.5              |                  |
| Width – in                           | 78.2               |                  |
| Height – in                          | 69.9               |                  |
| Track Width – in                     | 66.6               |                  |
| Tire Size – in                       | 15                 |                  |
| Shipping Weight – w/o fuel – lb      | 4470               |                  |
| Working Weight – w fuel – lb         | 5030               |                  |
| DIMENSIONS WITHOUT RUNNING GEAR      |                    |                  |
| Length – in                          | 104.2              |                  |
| Width – in                           | 60.7               |                  |
| Height – in                          | 61                 |                  |
| Shipping Weight – w/o fuel – lb      | 4207               |                  |
| Working Weight – w fuel – lb         | 4767               |                  |

## **Key Features**

- Versatility in application increases productivity and lowers total cost of ownership.
- Sturdy design includes corrosion-resilient galvanneal steel enclosure, A-frame drawbar and heavy-duty axles.
- Thermostatic clutch-driven cooling fan ensures quiet operation and cuts fuel costs by an average of 10% (in cold weather conditions.
- State-of-the-art control panel provides easy-to-use operator interface.
- Equipped with a Doosan-designed and manufactured airend that offers a highly efficient rotor profile, requiring less horsepower to deliver high-volume cfm output.
- Powered by a reliable Cummins QSB 4.5L engine that provides outstanding performance and productivity.





ATS EQUIPMENT INC.

**Construction Equipment & Supplies** 

**Rentals · Sales · Service** 

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200

CANDIA, NH (603) 483-2100