

ATS Equipment, Inc. located in four convenient locations.

Boston, MA Auburn, MA Rehoboth, MA Candia, NH

33 Locust Street 487 Washington Street 51 Fall River Avenue 133 Raymond Road

Tel: (617) 825-3600 Tel: (508) 832-8500 Tel: (508) 379-6200

Tel: (603) 483-2100





FEATURES

•4-700FT HOSES •THAW UP TO 5,600 FT2 •CURE UP TO 11,200 FT2 •TEMPORARY HEAT UP TO 12,000 FT2 •UP TO 120 HRS RUN TIME CSA/UL CERTIFIED PLC CONTROLLED SYSTEM •BI-DIRECTIONAL POWERED REEL WITH FREEWHEEL FEATURE •ON BOARD AIR COMPRESSOR FOR EVACUATING HOSES





DOUBLE LOOP TECHNOLOGY

BY USING SHORTER HOSES, MORE FLUID, AND HIGHER EFFICIENCY PUMPS WITH INCREASED FLOW, THE HEAT KING PROVIDES MORE CONSISTENT TEMPERATURE TO THE FIELD FOR BETTER CONCRETE **CURING AND GROUND THAWING** RESULTS.



HEAT KING ADVANTAGE



- GLYCOL GETS UP TO OPERATING TEMPERATURE FASTER THAN COMPETITORS (DESIG-NATED CIRCULATION PUMP PULLS FROM THE RESERVOIR AND DOESN'T HAVE TO PUSH COLD GLYCOL THROUGH THE FIELD HOSES)
- GLYCOL CAN BE BLOWN OUT OF THE FIELD HOSES AND STORED IN THE RESERVOIR. ELIMINATING THE NEED TO STORE IT IN A CONTAINER. CONVENIENT WHEN ABANDON-ING THE HOSES IN CONCRETE OR FOR SPACE HEATING SET-UPS & TAKE DOWNS
- TYING INTO EXISTING MANIFOLDS SUCH AS IN-FLOOR HEATING
- OIL & GAS APPLICATIONS SUCH AS TANK HEATING & HAVING THE ABILITY TO RETRIEVE THE GLYCOL FROM STEAM COILS
- GLYCOL CAN BE LEFT IN THE FIELD HOSES OR THE RESERVOIR

HK300 SPECIFICATIONS

- Hose
- Hose
- Supply Manifold
- Return Manifold
- Ground Thawing Capacity
- Concrete Curing Capacity

- Field Pump
- Circulating Pump
- Fuel Tank
- Run Time
- Fuel Consumption
- Flo Indicator

- 4 700 ft Field Hoses (5/8" Hose) Unspool with one person
- 4 1/2" quick connect & 1 1" quick connect
- 4 1/2" quick connect & 1 1" quick connect up to 5,600 ft²
- up to 11,200 ft²
- Temporary Heating Capacity 12,000 ft² (Varies with R-Value)
 - 1 Hp Centrifugal
 - 1/2 Hp Centrifugal
 - 192 US GAL
 - Up to 120 Hours
 - HK 300 = 2.24 GPH, Genset = .55 GPH
 - Ensures proper operation

- Interior Lights
- Mud Tray
- Heater Capacity Diesel
- Glycol Tank
- Electrical Requirements
- Generator (Optional)
- Axle
- Hitch
- Dimensions
- Weight (Fuel Empty/Full)
- Burner

Standard for ease of night operation Added under the reel to catch mud debris 311,000 BTU/H Heating Fuel Input

96 US GAL

2 - 120V AC 20A Circuits 1 - 7 kw or 1- 6 kw MQ

1 - 7,000lb Torsion Axle, Electric Brakes

2 5/16" Ball (Pintle also available)

14'x86"x83"

5,665 lbs / 7,009 lbs

Beckett Burner



ATS Equipment, Inc. located in four convenient locations.

Boston. MA Auburn, MA Rehoboth, MA Candia, NH

33 Locust Street 487 Washington Street 51 Fall River Avenue 133 Raymond Road

Tel: (617) 825-3600 Tel: (508) 832-8500 Tel: (508) 379-6200 Tel: (603) 483-2100