# heat wagon portable space vented heaters



**2730**C


www.atsequipment.com

# **Propane & Natural Gas**

## **SPECIFICATIONS**

SPECIFICATIONS		
Input	. 2,000,000 BTU	
Fuel	. Vapor Propane,	
	Natural Gas	
	Liquid Propane	
Inlet Pressure	. Max PS	Min PSI
	250 lbs.	10 lbs.
Gas Consumption	. 21.9 GPH	LP
	2000 CFH	NG
Electrical Requirements	. 208-240V 3Ø 30 Amp	
Fan		
	2" Static Pressure	
Thermostat	. High - Low	
Setting Range	. 110°F - 30°F	
Temp Rise	. 220°F	
Dimension	.72″L x 32″W x 46″H	

Approximate Weight......440 lbs.



### **Features**

- Air flow switch
- Burner heat shield
- Ductable
- Flame safeguard control
- Fused disconnect switch
- Hi limit switch
- Manifold pressure gauge
- Motor overload manual reset
- Panel mounted voltage meter
- Remote thermostat
- Weather sealed control box

### **Benefits**

- Safe fuel shutdown if combustion air is interrupted
- Low housing temperature
- May be ducted up to 200 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Direct wire with easy, safe 100% power shut off
- Protects heater by shutting down if unit is being overfired
- Helps in diagnosing specific gas flow problems
- Protects heater by shutting down if voltage is too low
- Easy monitoring of control voltage to ensure trouble-free operation
- Automatically cycles the heater high low to maintain room temperature
- Protected electrical components

ATS EQUIPMENT INC.

**Construction Equipment & Supplies** 

**Rentals • Sales • Service** 

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH, MA (508) 379-6200 CANDIA, NH (603) 483-2100