

AVAILABLE FOR RENT AT



www.atsequipment.com

S1505

Propane & Natural Gas

SPECIFICATIONS

Input.....	1,500,000 BTU/Hi Fire - 800,000 BTU/Lo Fire	
Fuel.....	Vapor Propane, Natural Gas	
Inlet Pressure	Max W.C.	Min W.C.*
Propane.....	14" w.c.	9" w.c.
Natural Gas.....	14" w.c.	9" w.c.
Manifold Pressure	Propane.	2.7" w.c.
	Natural Gas	7.2" w.c.
Gas Consumption	16.4GPHLP 1500CFHNG	
Gas Connection.....	1 1/4" NPT	
Electrical Requirements	120 Volts 20 amp circuit	
Fan	7000 CFM 1 HP	
Thermostat	HI - LO	
Temp Rise	350°F	
Shipping Dimensions.....	69"L x 32"W x 41.5"H	
Approximate Weight.....	300 lbs.	



Features

- AGA Certified
- Air flow switch
- Burner heat shield
- Dual fuel
- Flame safeguard control
- Hi limit switch
- Motor overload - manual reset
- Panel mounted thermostat
- Panel mounted voltage meter
- Stackable design
- Weather sealed control box
- 6" wheels, carrying bars & lifting loop

Benefits

- Tested to ANSI standard Z83.7 (1990)
- Safe fuel shutdown if combustion air is interrupted
- Low housing temperature
- Simple lever change from propane to natural gas
- Safe monitoring of combustion, one trial electronic ignition with 4.7 second shutdown
- Protects heater by shutting down if unit is being overfired
- Protects heater by shutting down if voltage is too low
- Automatically cycles the heater hi/lo
- Easy monitoring of supply voltage to ensure trouble-free operation
- Less need for large storage space
- Indoor/outdoor usage
- Easy relocation by one person

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100