



www.atsequipment.com

## **EASYCLEAN™ CONCRETE MIXER**

THE EASYCLEAN™ ADVANTAGE
Our polyethylene drums put an end
to clean up problems and save you
time and money. Removing dry
material from a steel-drum mixer,
may take several hours and result
in dents or damage in the process.
A simple tap with a rubber mallet
does the job — cleans out in
minutes without dents, rust or
cracks!



## **Features:**

- 6-cubic foot capacity
- Easy clean polyethylene drum
- Baldor 1.5-hp, 115/230V single-phase electric motor
- Heavy-duty one piece cast iron bull gear
- A wide opening for easy loading
- All mixers available with loop coupler, 2" ball coupler or pin-type coupler. Heavy duty safety chains are included.



## **Specifications:**

Model	MC64P
Capacity— cu.ft.	6
Capacity — bags	1/2
	1.5 HP 1ø 115/230V Elect.
Power Sources**	4.8 HP Honda
	7.9 HP Honda
Average weight* — lbs.	685
Length w/tongue x W x H — in.	102X51X59
Discharge height — in.	23
Drum opening — in.	19
Drum depth — in.	29
Tires	B78x13
Drive	V-Belt
Dump Action	Manual

<sup>\*</sup> Actual bag mix capacity based on a 94lb. bag of Portland cement. May vary depending on aggregate size and mix design.

ATS EQUIPMENT INC.

**Construction Equipment & Supplies** 

**Rentals · Sales · Service** 

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200

CANDIA, NH (603) 483-2100

<sup>\*\*</sup> Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.